

{phocagallery view=category|categoryid=59|imageid=1863|limitcount=1|detail=2|displayname=0|displaydetail=0|imageshadow=shadow1|bordercolor=#FFFFFF|bordercolorhover=#CC0000|float=left|displaydownload=0}

The AM3013T has both the measurement functions and the MicroTouch button to capture pictures directly from the Dino-Lite. The improved image sensor provides a high quality image with very natural colors and it also offers a high refresh rate for better real time images. It is an affordable solution for industrial, scientific and business use.

Model	AM3013T
Resolution	640x480pixels (VGA)
Magnification	10x~70x, 200x
Interface	USB 2.0, High speed USB transmission
Nr. of LED's	8
LED on/off switchable	√
LED color	White
Material	Composite
Microtouch	√
Output	
Picture, video and time-lapsed video	
Video Frame Rate	up to 30 frames-per-second, 15fps at 1.3M
Measurement	√(line, radius, circle, 3-point circle, etc.)
Calibration	-
Filter/Diffuser	-
Compatibility	Windows XP, Vista, 7 and recent MAC OS
Software (Included)	Windows: DinoCapture, Mac: DinoXcope
Special	
Other	Affordable solution for industrial, scientific and business use
<b>Product sheet</b>	<b>Download product sheet <a href="#">here</a></b>

{phocagallery view=category|categoryid=59|imageid=1863|limitcount=1|detail=2|displayname=0|displaydetail=0|imageshadow=shadow1|bordercolor=#FFFFFF|bordercolorhover=#CC0000|float=left|displaydownload=0}

Example Pictures: